

B-852 Mid-range Printer

Datasheet

- With powerful networking capabilities, the B-852 wide web printer from Toshiba delivers outstanding performance for a wide variety of environments and applications.
- This innovative industrial printer offers superior features including extremely fast processing, large internal memory, web printer controls and SNMP networking tools.



Speed and Functionality

The B-852 offers high-speed printing and enhanced processing via an extensive choice of interfaces – including USB 2.0 and internal LAN. The options of serial interfaces provide additional flexibility and choice, making the B-852 adaptable to the widest variety of environments and applications.

High Print Quality

The 216 mm printhead facilitates rapid printing of large format compliance labels in 300 dpi.





SPECIFICATIONS

General

Print Method Thermal transfer/Direct thermal

Printhead Flat head

Dimensions (W x D x H) 385 x 181 x 243 mm

429 x 427 x 265 mm with supply holder installed

Weight 15.6 kg

User interface LCD (16 digits), 3 x LED, 3 x key

Operating Temperature / Humidity

5°C to 40°C / 25-85% non condensing

Humidity relative humidity (RH) **Power Supply** AC 100 to 240 V, 50/60 Hz

Print

Resolution 300 dpi (11.8 dots/mm)

Maximum Print Speed 101.6 mm/second (4 ips)

Maximum Print Width 216.8 mm

Maximum Print Length 640 mm

Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128,

EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Postnet, RM4SCC, KIX-Code,

Customer Barcode, GS1 Databar

2D Codes Data Matrix, PDF417, QR Code, Maxi Code,

Micro PDF417, CD Code

Fonts Bitmap font, Outline font, Writable characters, TTF

Media

Alignment Centred

Backing Paper Width 100-242 mm

Label Thickness 0.13-0.18 mm

Inner Media Core Diameter 38-76 mm

Outer media Roll Diameter 230 mm

Media Type Roll, Fanfold

Software & Connectivity

Printer Driver Windows 10/8/7/Vista (32/64 bit),

Windows Server 2012/Server 2008 (32/64 bit)

USB 2.0 (Full Speed), LAN 10/100 Base, Parallel port, Serial port¹⁾

Language ModeTPCL, BCI (function)Label SoftwareBarTender UltraLite

Options

Interface

For B-852 Cutter module, expansion I/O board,

RTC (real time clock)

1) Optional



Ribbon

Ribbon Width 120-220 mm

Ribbon Core Size 25.4 mm (1 inch)

Fixed Core Length 240 mm

Max. Ribbon Length 300 m

Max. Ribbon Diameter 40 mm

For more information, please contact your local Toshiba partner.



Südstrasse 4a | 3110 Münsingen T: +41 31 838 50 50 | F: +41 31 838 50 55 info@labeltech.ch | labeltech.ch